

**OVER
24.5^{MWh}
Lifetime
Production**

TRUST EKOTEK'S
HIGH CAPACITY BATTERY WITH A
>15-YEAR DESIGN LIFE AND 9000+
AT 80% DOD



5 kWh+

8 Year Warranty

LiFePO₄
ORIGINAL BYD Cells



PRO CUBE 5 kWh+
Lithium Ion LiFePO₄ Battery

ET - 314-512/100

Features:

- Packed with high performance LFP single cell, long life, safety and wide temperature range
- High energy density, small size, light weight, no pollution
- Packing with single cell container, fire retardant wire and laser welding, stable and safe
- Built-in BMS, with battery voltage, current, temperature and health management
- LED indicate the battery SOC and operating status
- LCD Screen display the battery voltage, current, temp., SOC detail information
- Built-in Fire Arrestors
- Loose Connection Detection
- Auto Detection (Automatically Detects Inverter)
- Active Cell Balancing
- Set different communication protocols through 5 inch LCD touch screen
- Dust/Water/Weather protection for all cable connectors with plastic covers
- Built in WiFi and Bluetooth Modules
- Support communication with solar inverter by CAN 2.0
- Update firmware by RS485 port
- Support 100 units in parallel and communicate by RS485/CAN 2.0
- More than 15 years design life
- Stable performance, maintenance-free

 LCD Touch SCREEN	48V SYSTEM VOLTAGE	100A DISCHARGE
 AUTO DETECT INVERTER TYPE	 WIRELESS CONNECTIVITY THROUGH APP	
 BUILT-IN FIRE ARRESTORS	 LOOSE CONNECTION DETECTION	 ACTIVE CELL BALANCING

CONNECT UPTO 100 BATTERIES IN PARALLEL





PRO CUBE 5 kWh+		
BATTERY SPECS		
Battery Chemistry		LiFePO ₄
Voltage	Nominal @ 25 °C ~ 0.2 °C	51.2 V
Capacity	Nominal @ 25 °C ~ 0.2 °C	100 Ah
Energy (Wh)		5120 Wh
Module Weight ±0.5 kg		49 kg
Dimensions (W x D x H) mm, ±2 mm		640 x 420 x 157
Cell Serial Number (pcs)		16, Active Cell Balancing
OPERATING PARAMETERS		
Voltage Range		44.8 V ~ 56.8 V
Charging Voltage		56 ± 0.8 V
Charging Current		100 A Maximum
Discharging Voltage		44.8 V
Discharging Current		100 A
Peak Discharge (25°C)		300 A, 3 S
Recommended Depth of Discharge		80.0%
Display		5 inch touchscreen LCD display, set protocol on LCD; 4 LEDs for SOC 1 LED for Run status 1 LED for ALM
BATTERY MANAGEMENT SYSTEM		
BMS	Built-in BMS	Yes
Communication Port (can be customized)		CAN 2.0, RS458, WiFi, Bluetooth
Scalability (Max. In 1 battery group)		100 units in parallel
GENERAL		
IP Rating of Enclosure		IP21
Design Life	Service Life @ 25 °C	> 15 Years
Cycle Life	Service Life @ 25 °C	> 6000 Times
Certifications		MSDS, UL1973, IEC62619, CE, UN38.3